

SUPERFLOW

SUPERFLOW



FELLOW

INTERGAS[®]
BOILERS

WWW.INTERGASVERWARMING.NL

CUTTING-EDGE HOT WATER

INTERGAS[®]
BOILERS



CUTTING-EDGE
COMFORT



SUPERFLOW

FLOW

Cutting-edge comfort

If you'd like to shower with an uninterrupted supply, or run hot water from multiple taps at the same time, then Intergas's Superflow is the perfect solution. Superflow is the latest innovation in high-efficiency instantaneous hot water systems, based on the same tried-and-tested Intergas technology at the core of our entire Kombi Kompakt range. A constant supply of hot water at a consistent temperature guaranteed. And no water storage tank in sight.

Innovative Heat Exchanger

Superflow utilizes our own tried-and-tested and patented heat exchanger technology that incorporates a fully integrated copper coil, ensuring maximum heat transfer and minimal heat loss.

The cold water supply flows directly through the heat exchanger to cool and condense flue gases fully and extract as much heat as possible.

We built the same heat labyrinth into our Superflow heat exchanger as we used in the Kombi Kompakt HReco to achieve unrivalled performance.

**CUTTING-EDGE
INNOVATION**

The Superflow contains cutting-edge, solid-state electronics to control its gas valve, pilot light and fan. By doing so, we've succeeded in reducing the number of moving parts and increasing reliability still further.



INNOVATION

XXL Comfort

Our Superflow boiler has all the advantages of a water storage tank system, but none of its disadvantages. In short, an uninterrupted supply of hot water and high efficiency for your enjoyment and comfort. The Superflow is available in two models (45 or 60 kW), one of which will be perfect for all your hot water requirements. The 60-kW model delivers up to 26 L/min at 40 °C, putting it in the XXL category.



Technical Specifications

The Superflow is available in two models, both of which supply an ample flow of hot water and one of which will be perfect for all your hot water requirements. All of our Superflow appliances are A-label rated for hot water usage.



		SUPERFLOW 45	SUPERFLOW 60
Rated output	kW	45	60
Load profile	-	XXL	XXL
Energy efficiency rating (hot water)	-	A	A
Min. flow rate	l/min	1,5	1,5
Hot water flow rate (60 °C)	l/min	12,5	15,5
Hot water flow rate (40 °C)	l/min	21,5	26
Weight	kg	27,5	30
Height	mm	760	760
Width	mm	400	450
Depth	mm	260	260

Technical specifications subject to change



CUTTING-EDGE
HOT WATER